

# Request for Quotation Form

---

Please fill in this form as completely as you can. We will respond within one business day after receipt.  
Required fields are marked with an asterisk (\*).

## Contact Info:

\*Company name: \_\_\_\_\_ Date: \_\_\_\_\_  
\*Contact: \_\_\_\_\_ Title: \_\_\_\_\_  
\*Telephone: \_\_\_\_\_ Fax: \_\_\_\_\_  
Email: \_\_\_\_\_

## Billing:

## Ship to (if different):

Address: \_\_\_\_\_  
City: \_\_\_\_\_  
State: \_\_\_\_\_  
Zip code: \_\_\_\_\_

---

## Product Info:

\*Commodity (select one):

- |   |  |
|---|--|
| <input type="checkbox"/> Black Plate, Double Reduced/ASTM: A625-98                  | <input type="checkbox"/> Stainless Steel Strip/ASTM: A240-96       |
| <input type="checkbox"/> Black Plate, Single Reduced/ASTM: A650-98                  | <input type="checkbox"/> TFS (Chromium Coated Steel)/ASTM: A657-98 |
| <input type="checkbox"/> Cold Rolled Strip Steel/ASTM: 109-91                       | <input type="checkbox"/> Tin Coated Sheet/ASTM: A599-92            |
| <input type="checkbox"/> Cold Rolled Steel/ASTM: A366-97; 620-97;<br>963-97; 969-97 | <input type="checkbox"/> Tin Plate, Double Reduced/ASTM: A624-95   |
| <input type="checkbox"/> Electro Galvanized Steel/ASTM: A591-98; 879-96             | <input type="checkbox"/> Tin Plate; Single Reduced/ASTM: A626-95   |
| <input type="checkbox"/> Hot Dipped Galvanized Steel/ASTM: A653-98                  | <input type="checkbox"/> Other: Fill in box below                  |

Other: \_\_\_\_\_

End Use: \_\_\_\_\_

**Berlin Metals**  
**ISO 9001 Certified**

Email: Sales@BerlinMetals.com • Phone: 800/754-8867 • Fax: 219/933-0692  
3200 Sheffield Avenue • Hammond, Indiana 46327

## Berlin Metals

### Alloy/Chemistry:

#### Carbon Steels:

- 1008/1010 Low Carbon Steel
- 1050 High Carbon Steel Strip
- 1075 High Carbon Steel Strip

#### Stainless Steels:

- |                               |                                      |
|-------------------------------|--------------------------------------|
| <input type="checkbox"/> 301  | <input type="checkbox"/> 316L        |
| <input type="checkbox"/> 302  | <input type="checkbox"/> 321         |
| <input type="checkbox"/> 304  | <input type="checkbox"/> 409         |
| <input type="checkbox"/> 304L | <input type="checkbox"/> 430         |
| <input type="checkbox"/> 305  | <input type="checkbox"/> Other _____ |

\*Thickness: \_\_\_\_\_

#### Tolerance (+/-):

- |                                   |                                      |
|-----------------------------------|--------------------------------------|
| <input type="checkbox"/> +/-10%   | <input type="checkbox"/> +/-0.0015   |
| <input type="checkbox"/> +/-5%    | <input type="checkbox"/> +/-0.002    |
| <input type="checkbox"/> -8%+5%   | <input type="checkbox"/> Other _____ |
| <input type="checkbox"/> +/-0.001 |                                      |

### \*Finish:

#### Tin Mill Products:

- 5C Unmelted "Matte"
- 5C Melted "Silver" or "SBF"
- 7C Melted "Stone" or "Bright"
- 7C Unmelted
- 5C "Matte"
- 7C "Bright"

#### Hot Dipped Galv.:

- Zero Spangle
- Extra Smooth
- Min. Spangle
- Regular Spangle

#### Stainless Steels:

- 2B
- 1BA
- 2D

#### Cold Rolled:

- Dull, Matte, Number 1
- Bright, Number 2
- Best Bright, Number 3

### Coating:

#### Tin Plate:

- 10 (1.1/1.1)
- 20 (2.2/2.2)
- 20/05 (2.2/0.55)
- 20/10 (2.2/1.1)
- 25 (2.8/2.8)
- 50 (5.6/5.6)
- 50/20 (5.6/2.2)
- 50/25 (5.6/2.8)
- 75 (8.4/8.4)
- 72/20 (8.4/2.2)
- 75/25 (8.4/2.8)
- 100 (11.2/11.2)

#### Electro Galv.:

- Class A: Light
- Class B: Standard Coat
- Class C: Double Coat

#### Hot Dipped Galv.:

- G30
- G40
- G60
- G90

Other: \_\_\_\_\_

**Berlin Metals**  
**ISO 9001 Certified**

Email: Sales@BerlinMetals.com • Phone: 800/754-8867 • Fax: 219/933-0692  
Corporate Headquarters • 3200 Sheffield Avenue • Hammond, Indiana 46327

**Berlin Metals**

**\*Temper/Hardness:**

**Tin Mill Products:**

- T-1: 53 Max HR 30T
- T-2: 53 +/- 4 HR30T
- T-3: 57 +/- 4 HR30T
- T-4: 61 +/- 4 HR30T
- T-5: 65 +/- 4 HR30T
- DR-8: 72 Nom HR30T
- DR-9: 75 Nom HR30T
- DQ: 55 Max HRB
- CQ: 65 Max HRB

**Stainless Steels:**

- Annealed
- ¼ Hard
- ½ hard
- ¾ hard
- Full Hard
- Spring Temper

**Carbon Steels:**

- Full Hard, #1 Temper: 84 Min HRB
- Half Hard, #2 Temper: 70-85 HRB
- ¼ Hard, #3 Temper: 60-75 HRB
- Temper Rolled, CQ, #4 Temper: 65 Max HRB
- Dead Soft, DQ, #5 Temper: 55 Max HRB
- CS (CQ)
- DS (DQ)
- DDS (DDQ)
- EDDS (EDDQ)

Other: \_\_\_\_\_

**\*Slit Width:** \_\_\_\_\_

Tolerance (+/-):

- +/- .005"
- 0/+ .010"
- Other

Other: \_\_\_\_\_

Length: \_\_\_\_\_

Tolerance (+/-): \_\_\_\_\_

**\*Quantity:** \_\_\_\_\_

**Targets:**

Required by date: \_\_\_\_\_

Release period: From: \_\_\_\_\_ To: \_\_\_\_\_

Typical release quantity: \_\_\_\_\_ Annual usage: \_\_\_\_\_

Current supplier: \_\_\_\_\_ Target or competitive price: \_\_\_\_\_

**Berlin Metals**

**Processing and Packaging Requirements:**

I.D. Cores:

- Yes
- No

Coil I.D.:

- 16"
- 20"
- Other \_\_\_\_\_

Minimum coil O.D.: \_\_\_\_\_

Maximum coil O.D.: \_\_\_\_\_

Maximum coil weight: \_\_\_\_\_

Maximum skid weight: \_\_\_\_\_

Maximum skid height: \_\_\_\_\_

Spacers:

- 1"
- No
- Other \_\_\_\_\_

Eye:

- Vertical
- Horizontal

Wrap:

- Stretch wrap
- Bag
- Bare
- Other \_\_\_\_\_

Truck loading:

- Rear
- Side

Receiving hours: \_\_\_\_\_

Appointment required:

- Yes
- No

Freight:

- Collect
- Prepaid

Preferred carrier: \_\_\_\_\_

Certifications required:

- Yes
  - No
- 

**Berlin Metals**  
**ISO 9001 Certified**

Email: Sales@BerlinMetals.com • Phone: 800/754-8867 • Fax: 219/933-0692  
Corporate Headquarters • 3200 Sheffield Avenue • Hammond, Indiana 46327

## Berlin Metals

**Miscellaneous:**

Mechanical Properties:

Tensile: \_\_\_\_\_

Yield: \_\_\_\_\_

Elongation: \_\_\_\_\_

*Other physical or mechanical properties:*

Passivation:

- Yes
- No

Oiling:

- Yes
- No
- Standard
- Light
- Heavy
- Specific type: \_\_\_\_\_

Other Comments:

---

---

---

---

**Berlin Metals**  
**ISO 9001 Certified**

Email: Sales@BerlinMetals.com • Phone: 800/754-8867 • Fax: 219/933-0692  
Corporate Headquarters • 3200 Sheffield Avenue • Hammond, Indiana 46327